## Sec. 74-84. - Schedule of dimensional regulations.

	<u>Mini</u>	Lot mums				nimur etbacł	<u>m Yard</u> ‹s <sup>6 &amp; 7</sup>					
Distri ct	Area (squa re feet)	Widt h (feet )	Dept h (feet )	Density Maximu m Dwellin g Units per acre	Fro nt (fee t)	Side (fee t)	Rear (feet)	Minimu m Offstre et Parking per Dwellin g Unit <sup>1</sup>	Maximu m Height <sup>3</sup> (feet)	Floo d Zon es	Minimu m Living Area per Unit <sup>2</sup> (square feet)	Floor Area Ratio (FAR) <sup>6</sup>
RE	18,00 0	100	100	2	25	7.5 4	25 feet or 20% of lot depth, whichev er is less	2	32	34	2,000	_
<mark>R-1</mark>	<mark>10,00</mark> 0	80	100	4	25	<mark>7.5</mark> 4	25 feet or 20% of lot depth, whichev er is less	2	32	34	<mark>1,200</mark>	_
R-2	7,500	75	90	4	25	7.5	25 feet or 20% of lot depth,	2	32	34	1,000	_

The schedule of dimensional regulations for the various zoning districts is as follows:

							whichev er is less					
RM- 10 <sup>5</sup>	5 acres	_	_	10	25	15 <sup>4</sup>	25	1.5	32	34	1,500	_
RM- 15	10,00 0	100	100	15	25	7.5 4	15	1.5	32	34	1,000	_
RPD	5 acres		_	5	74-83		section	1	32	_	1,200	_
Н	17.5 acres		_	28	74-83		section	1	32	34	300	0.4
C-1	12,00 0	100	100	None	25	12	10	1	32	34	N/A	0.35
C-2	10,00 0	80	100	None	25	12	10	1	32	34	N/A	0.35
C-3	10,00 0	80	100	None	25	12	10	1	32	34	N/A	0.30
C-4	10,00 0	80	100	None	25	12	10	1	32	34	N/A	0.5
GC	_	Non e	Non e	None	25	25	25		32	34	N/A	Town Commissi on Approval
C-5	10,00 0	Non e	Non e	None	10	5	10	1	32	34	N/A	0.5
SPM	10,00 0	80	100	25	25	25	25	1	32		N/A	0.30

PMU	17.5 acres		See section 74-85 for standards applicable to the planned mixed use (PMU) district
Ρ	consist regulat necess lands. l	ent wi tions sl ity for Howev	ssion shall establish dimensional regulations for the public district th the public land use of lands within this district. The dimensional hall be based upon need for harmonizing public use of the land with protecting the public's safety, health and welfare by the use of such ver, in no case shall the floor area ratio exceed 0.65 for institutional for transportation/utility related uses.

<sup>1</sup> See article III, division 3, of this chapter, pertaining to Off-street parking regulations.

<sup>2</sup> Exclusive of garages, breezeways, proches and patios.

<sup>3</sup>The height regulations contained in this section shall mean 32 or 34 feet from grade to the highest finished roof surface in the case of a flat roof, or to a point at the midpoint of the highest sloped roof, except for chimneys, parapets, bell towers and elevator penthouses. In no chase shall a structure exceed 45 feet in height except in a RPD or RM-10 zoned district. Building height limitations for flood zone area construction are as follows: Any property which is located within an area of special flood hazard as designated on flood hazard boundary map or a flood insurance rate map, shall measure the maximum height standard from the base flood elevation (BFE) of the flood zone the sstructure is located within. This shall not apply to any property located in the RPD district existing at the tim eof adoptio of this land development code. See subsection 74-83 (a)(3) for special height bonus provisions for RM-10 district.

<sup>4</sup> See section 74-113.

<sup>5</sup> See subsection 74-83(a) for additional requirements for RM-10 district.

<sup>6</sup> For impervious surface ratio, see section 74-112.

<sup>7</sup> On waterfront lots, all bildings, including gues cotages and servants quarters, shall be set back a minimum of 20 feet from the mean highwater mark or the seawall.

<sup>8</sup> All setbacks are measured from property lines except as noted.

(Ord. No. 300, § III(2.02.04), 11-7-90; Ord. No. 318, § 5, 6-2-92; Ord. No. 328, § B(2.02.04), 8-3-93; Ord. No. 342, § I, 11-2-93; Ord. No. 363, § 2, 3-19-96; Ord. No. 399, § 1, 11-20-01; Ord. No. 491, § 3, 4-15-14; Ord. No. 495, § 2, 4-1-14; Ord. No. 497, § 3, 6-17-14)