

DRAFT

Sec. 74-287. - Fences and fence walls.

- (a) All fences shall comply with the provisions of the Standard Building Code, 1988 edition, Section 1205, Appendix D, or subsequent editions~~-, and subject to the Town of Belleair property maintenance provisions, Article VIII, Section 74-517 of the Code of Ordinances.~~
- (b) The posts of each fence must be resistant to decay, corrosion and termite infestation. Wood fence posts shall be pressure treated or otherwise preserved.
- (c) Fence walls may be constructed of concrete, concrete block, stone, brick or any suitable masonry material. Concrete and concrete block walls shall be finished with a painted stucco finish on both sides. All perimeter retaining walls that are visible from public rights-of-way or open spaces/parks shall require caps.
- (d) Fences and fence walls may be located in side, rear and secondary front yard setback areas and shall not exceed the height of six feet except as otherwise provided in this section, exclusive of decorative supporting posts which may extend no more than nine inches above the maximum six-foot height of the fence or fence wall; provided, however, any fence or fence wall placed along any property line which abuts the Pinellas Trail may not exceed ten feet in height.
- (e) Fences, and fence walls, and hedges within ten feet of the mean high-water line or sea wall shall be no more than 48 inches in height.
- (f) The height of a fence or fence wall shall be determined from grade to the average top elevation of the fence or fence wall. Landscape berms, in conjunction with fences, shall be included in height determinations. Fences and fence walls shall be of uniform height along a running face, as topography allows, unless prohibited by other requirements of this code
- ~~(e)~~ (g) Fences and fence walls shall be prohibited within the front yard setback area and within the primary front yard setback area of corner parcels.
- ~~(f)~~ (h) In areas where the property faces two roadways, or is located in any other area construed to be a corner lot, no fence, ~~or~~ fence wall, or landscape buffer shall be located in the ~~vision~~ clear visibility triangle.
 - (1) No fence, wall, gate or landscape buffer shall not be allowed to constitute a visual obstruction to motorists, pedestrians or bicyclists, upon the streets, roads, sidewalks, bike paths, driveways and alleyways of the Town.
- (i) Except as provided in subsections (c) and (k), fences and walls may be constructed of wood, masonry, composite materials, vinyl, metal or wire, and shall be constructed of one material type only, except where specifically permitted herein, or by approval of the Town Manager.
- ~~(g)~~ (j) Fences shall be placed with the finished side out.

~~(h)~~ (k) Chain-link fences with canvas (or similar material) backing or mesh may only be permitted as a temporary construction fence, or on any parcel zoned Public District. Except as provided below, all chain-link fences shall either:

- (1) Be shielded on the exterior side (the side facing out) as to completely obscure the fence by a hedge or similar planting; or
- (2) Be coated with a ~~green or~~ black vinyl coating. Green vinyl coatings may only be used for properties zoned Public District; and
- (3) Have a top rail.

All fences, ~~including chain-link fences~~, or fence walls placed along a front yard setback or a primary front yard setback or along or within a secondary front yard setback area shall be shielded on the exterior side (the side facing out) by a hedge or similar planting. Any planting must grow to shield said fence over 85 percent of its surface within two years of planting. Should the shielding material die or be destroyed below the 85 percent coverage standard it shall, upon notification by the city, be replaced immediately or the city may take code enforcement action as provided in Division 4 of Article II.

~~(i)~~ (l) No fence or fence wall shall be constructed or installed in such a manner as to adversely affect drainage on or adjacent to the site. To provide adequate drainage or to prevent the obstruction of drainage on or adjacent to the site, a fence or fence wall may be constructed so as to allow the bottom of the fence or fence wall to begin no more than two inches above the ground without being in violation of the maximum height restrictions set out in subsections ~~(c) and (d)~~, (e) and (f) of this section.

~~(j)~~ (m) Any fence or fence wall required to be shielded by a hedge or similar planting shall be shielded by plant material approved by the town and such plant material shall be, at minimum, a size equivalent to a three-gallon plant and each such plant shall be planted not more than two feet apart. In addition, any fence or fence wall which is required to be shielded by a hedge or similar planting as provided in this section must be set back off a property line a sufficient distance to allow for the planting and growth of the hedge or similar planting and for the maintenance thereof.

- (1) The Town Manager may waive the requirement for fence or walls to be shielding with plant material depending on the fence or fence wall materials, or zoning district.
- (2) All chain-link fences must meet the 85 percent vegetative planting requirement at the time of installation. The Town Manager may waive this requirement for properties zoned Public District, where the fencing is used around recreational play fields.
- (3) Any fence or fence wall requiring vegetative planting must provide or demonstrate a means of irrigation acceptable to the Town, at the time of installation.

DRAFT

~~(k) Fences, and fence walls, and hedges within ten feet of the mean high water line or sea wall shall be no more than 48 inches in height.~~

~~(l)~~ (n) Electrically charged and, barbed wire or razor wire fences, or any fence or wall containing broken glass, or other substances reasonably calculated designed to do bodily harm fences are prohibited.

(o) New sections of fence being installed shall require the removal of the old sections. Old sections of fence shall not be abandoned in place.

(p) Temporary fencing during construction is permitted and regulated in Chapter 74, Division 4 of the Code of Ordinances. Once a building permit is closed or becomes inactive, the temporary construction fencing shall be removed. The parcel may remain without a fence, or a permanent fence can be erected pursuant to this section, and other sections of the Code, as applicable.